То	
The Manager ()	
CESC Ltd	Date:
Sub: Certificate Of Fitness For Grid-Connected Solar PV G Arrangement	enerating System Under Net-Metering / Net-Billing
Sir/Madam,	
This has reference to my/our application no PV Generating System (SPGS) under net-meterin	dated for installation of Grid-connected Solaring / net-billing arrangement.
tests were carried out to determine correct op power quality parameters of the SPGS, as specifi	stallation of the grid connected SPGS and necessary peration of islanding, generation of harmonics and ed in the West Bengal Electricity Regulatory Commission ewable Sources of Energy) Regulations, 2013 as amended of the certificate of fitness is enclosed herewith.
	operate the SPGS in a manner such that it does not tribution network of CESC Ltd. I/We further confirm ct its operation adversely.
Signature of the Eligible Consumer	
Name of the Eligible Consumer	
Consumer/Customer Id	
Enclosures:	
Certificate of Fitness Test Reports	



CERTIFICATE OF FITNESS

SPGS of ___ kW

Date	٥f	Instal	latic	'n.
Date	OI.	เบเรเนเ	Iauc	,,,,

Place:

Solar Module Model No.	Make:	No. of Modules:	Total Capacity (kW):
Solal Module Model No.	iviane.	Individual Capacity:	Total Capacity (KVV).
Inverter Details:	Make:	Model No.:	
No. of London London	ACCOUNT OF THE	Tabal AC assessible of	Control No. (c)
No. of Inverters Installed:	AC Capacity of individual Inverter (kW):	Total AC capacity of Inverter (kW):	Serial No(s).:
	miverter (KVV).	mverter (kvv).	
GPS Co-ordinates of the SPGS	Installation:	SPGS with battery back-u	p:
		(Yes/No)	
1	Installed at premises no	, Kolkata	_
[Pursuant to our engagem	nent by [name	e of Eligible Consumer], we	have inspected the above
captioned SPGS on] "or" [I / We, [name of the B	Eligible Consumer], have car	ried out the test in presence
of representatives of CESC	Limited on		·
or representatives or ease			
Upon such inspection it is	hereby certified that the SP	GS with installed capacity of	of kW, manufactured
by, confor	ms to the specifications r	mandated by the West Be	engal Electricity Regulatory
Commission (Cogeneration	and Generation of Electricit	ry from Renewable Sources o	of Energy) Regulations, 2013
as amended by the First A	Amendment Regulations, 20	020 (hereinafter for brevity	y's sake referred to as 'the
Regulations'). In particula	r and without prejudice to	o the foregoing, the said	SPGS conforms to correct
	eration of harmonics and ot		
	S is found to be technically		
network of the Distribution	·		,
network of the Distribution	T LICENSEC.		
This certificate is valid for a	period of one year and is su	ubject to periodic renewal. T	he validity of this certificate
is further subject to opera	tion, maintenance and rect	ification of any defect in th	ne SPGS in a manner which
ensures that its connectivi	ty does not pose any threat	or damage to the distribution	on network.
[Signature with sea	I]		
Of the Authorited Manda	/ Flicible Consumer		
Of the Authorized Vendor	/ Eligible Consumer		
Date :			ESC HOUS



Test Format for <u>Issuance of Certificate of Fitness of Solar Power Generating System (SPGS)</u>

eference No. :	•••••						Date :	• • • • • • • • • • • • • • • • • • • •
onsumer Name	:							
Consumer No	:							
ddress	:							
est for	:	New Installe	ation / Perioc	ic Check	ina (√the	e appropri	iate)	
etails of Solar PV G	enera				9 (, ,	
Solar Module Mode		Make:			of Module		Total Ca	apacity (kW _p):
				Indiv	<u>ridual Car</u> T	•	1010100	<u>πρασιίγ (κττρ).</u>
Inverter Details:		Make:			Model	No.:		
AC Capacity of Inv	erter (k	(W):		SPS (up to	6 decima	l places):		
Inverter Serial No.:						ck-up: Yes/ attery:	' No (√ the app	ropriate)
e performance/fo					D) / C			
		62116/IEC 61	727) :	Ok	/ Not Ok	: ($$ the ap	propriate)	
							propriate)	
o) % THD in Voltage	e - Me	asured at			ad-off co			
o) % THD in Voltage Permissible Voltage (As per IEEE	e - Me	asured at ortion Limits 2014)			ad-off co	ondition: Itage Dista	ortion	
o) % THD in Voltage Permissible Voltage	e - Me	asured at		during lo	ad-off co Vo Voltage	ondition: Itage Distoret Level:	ortion 	Overall
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV	e - Me	asured at portion Limits 2014) THD (%) 8.0	hours,	during loo	ad-off co	ondition: Itage Dista	ortion	Overall
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV 1kV < V <= 69 kV	ge Disto	asured at portion Limits 2014) THD (%) 8.0 5.0	Condition SPGS OF SPGS OF	during loo	Vo Voltage	ondition: Itage Dista E Level : THD (% Y-N	ortion 5) Measured B-N	Overall
Permissible Voltage (As per IEEE Voltage Level V <1.0 kV 1kV <v<= 69="" <v<="161" kv="" kv<="" td=""><td>e - Mer ge Dista E 519 : 2</td><td>asured at portion Limits 2014) THD (%) 8.0 5.0 2.5</td><td>Condition SPGS OF SPGS OF As per IEEE</td><td>during loon REF N E-519: Ok,</td><td>Vo Voltage -N /Not Ok(</td><td>Itage Distored Level: THD (% Y-N</td><td>Measured B-N Driate)</td><td></td></v<=>	e - Mer ge Dista E 519 : 2	asured at portion Limits 2014) THD (%) 8.0 5.0 2.5	Condition SPGS OF SPGS OF As per IEEE	during loon REF N E-519: Ok ,	Vo Voltage -N /Not Ok(Itage Distored Level: THD (% Y-N	Measured B-N Driate)	
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV 1kV < V <= 69 kV 69 kV < V <= 161 kV Power Generated	ge Disto E 519 : 2	asured at ortion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available)	Condition SPGS OF SPGS OF As per IEE	during loon Rift North Colon Colon Rift North Colon Co	Vo Voltage -N /Not Ok(\very panel /	Itage Distance Level: THD (% Y-N	Measured B-N Doriate)	. Watt
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV 1kV < V <= 69 kV 69 kV < V <= 161 kV Power Generated	ge Disto E 519 : 2	asured at ortion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available)	Condition SPGS OF SPGS OF As per IEE	during loon Rift North Colon Colon Rift North Colon Co	Vo Voltage -N /Not Ok(\very panel /	Itage Distance Level: THD (% Y-N	Measured B-N Doriate)	
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV 1kV < V <= 69 kV 69 kV < V <= 161 kV Power Generated Current by SPGS (decease)	e - Mer ge Dista E 519 : 2	asured at prition Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available SPGS ON without the control of	Condition SPGS OF SPGS OF As per IEE e in the invertional conditions.	during loon REF NE-519: Ok , ter displanasured :	Vo Voltage -N /Not Ok(\nimega) y panel /	Itage Distance Level: THD (% Y-N the appropriate of the propriate of the control of the c	ortion 5) Measured B-N oriate) c) Inverter Dis	. Watt
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV 1kV < V <= 69 kV 69 kV < V <= 161 kV Power Generated Current by SPGS (dec) Manual Isolation	ge Disto E 519:2 / by SPC during S	asured at ortion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the strength of the strength	Condition SPGS OF SPGS OF As per IEE The in the invertional invert	during loon asured :	Voltage Voltage Voltage Voltage Voltage Voltage	Itage Distance Level: THD (% Y-N the approprometer of the approprometer) the approprometer approprometerA	ortion S) Measured B-N oriate) c):	. Watt play :
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV 1kV < V <= 69 kV 69 kV < V <= 161 kV Power Generated Current by SPGS (dec) Manual Isolation	ge Disto E 519:2 / by SPC during S	asured at ortion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the strength of the strength	Condition SPGS OF SPGS OF As per IEE The in the invertional invert	during loon asured :	Voltage Voltage Voltage Voltage Voltage Voltage	Itage Distance Level: THD (% Y-N the approprometer of the approprometer) the approprometer approprometerA	ortion S) Measured B-N oriate) c):	. Watt play :
Permissible Voltage (As per IEEE Voltage Level V <1.0 kV 1kV <v<= (dec)="" 69="" <v<="161" by="" current="" d)="" generated="" isolation="" kv="" manual="" observation<="" other="" power="" spgs="" td=""><td>ge Disto E 519 : 2 by SPC during S in Switc</td><td>asured at ortion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the strength of the strength</td><td>Condition SPGS OF SPGS OF As per IEE The in the invertional invert</td><td>during loon asured :</td><td>Voltage Voltage Voltage Voltage Voltage Voltage</td><td>Itage Distance Level: THD (% Y-N the approprometer of the approprometer) the approprometer approprometerA</td><td>ortion S) Measured B-N oriate) c):</td><td>. Watt play :</td></v<=>	ge Disto E 519 : 2 by SPC during S in Switc	asured at ortion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the strength of the strength	Condition SPGS OF SPGS OF As per IEE The in the invertional invert	during loon asured :	Voltage Voltage Voltage Voltage Voltage Voltage	Itage Distance Level: THD (% Y-N the approprometer of the approprometer) the approprometer approprometerA	ortion S) Measured B-N oriate) c):	. Watt play :
Permissible Voltage (As per IEEE Voltage Level V <1.0 kV 1kV <v<= (dec)="" (e)="" 69="" <v<="161" by="" current="" d)="" equipment="" generated="" i<="" isolation="" kv="" manual="" observation="" other="" power="" spgs="" td="" test=""><td>e - Mer ge Diste E 519 : 2 by SPC during S an Switc ions/Re</td><td>asured at portion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the for Battery Between the semants (if any)</td><td>Condition SPGS OF SPGS OF As per IEE Te in the invertibut load): Me ack-up System</td><td>during loon R F N E-519: Ok, ter display asured: m: Ye</td><td>Vo Voltage -N /Not Ok(√ y panel /</td><td>Itage Distance Level: THD (% Y-N I the appropriate of the approp</td><td>ortion (5) Measured B-N oriate) (1):</td><td>. Watt play :</td></v<=>	e - Mer ge Diste E 519 : 2 by SPC during S an Switc ions/Re	asured at portion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the for Battery Between the semants (if any)	Condition SPGS OF SPGS OF As per IEE Te in the invertibut load): Me ack-up System	during loon R F N E-519: Ok, ter display asured: m: Ye	Vo Voltage -N /Not Ok(√ y panel /	Itage Distance Level: THD (% Y-N I the appropriate of the approp	ortion (5) Measured B-N oriate) (1):	. Watt play :
Permissible Voltage (As per IEEE Voltage Level V <1.0 kV 1kV <v<= (19)="" (19)<="" (dec.)="" (e)="" 69="" <v<="161" by="" current="" d)="" equipment="" generated="" isolation="" kv="" manual="" observation="" other="" power="" spgs="" td="" test=""><td>e - Merge Dista ge Dista E 519 : 2 by SPC during S in Switc ions/Re Used: ; M</td><td>asured at portion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the series of t</td><td>Condition SPGS OF SPGS OF SPGS OF As per IEE out load): Me ack-up System; SI No</td><td>during loon REF NE-519: Okyter displanasured :</td><td>Voltage -N /Not Ok(√ y panel /</td><td>the approprime Appropr</td><td>ortion S) Measured B-N Oriate) c): Inverter Disportate) ration Details</td><td>. Watt play :</td></v<=>	e - Merge Dista ge Dista E 519 : 2 by SPC during S in Switc ions/Re Used: ; M	asured at portion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the series of t	Condition SPGS OF SPGS OF SPGS OF As per IEE out load): Me ack-up System; SI No	during loon REF NE-519: Okyter displanasured :	Voltage -N /Not Ok(√ y panel /	the approprime Appropr	ortion S) Measured B-N Oriate) c): Inverter Disportate) ration Details	. Watt play :
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV 1kV < V <= 69 kV 69 kV < V <= 161 kV Power Generated Current by SPGS (dec) Manual Isolation d) Other Observation (e) Test Equipment I	e - Merge Distrete E 519 : 2 / by SPC during Strain Switch ions/Refused:; Mut By	asured at portion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the second of t	Condition SPGS OF SPGS OF SPGS OF As per IEE Out load): Me ack-up System System SI No	during loon REF NE-519: Okyter displanasured :	Vo Voltage -N /Not Ok(√ y panel /	the approprime Appropr	ortion 5) Measured B-N oriate) cl): : Inverter Disporiate)	. Watt play :
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV 1kV < V <= 69 kV 69 kV < V <= 161 kV Power Generated Current by SPGS (dec) Manual Isolation d) Other Observation (E) Test Equipment I	e - Merge Distrete E 519 : 2 / by SPC during Strain Switch ions/Refused:; Mut By	asured at portion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the series of t	Condition SPGS OF SPGS OF SPGS OF As per IEE Out load): Me ack-up System System SI No	during loon REF NE-519: Okyter displanasured :	Voltage -N /Not Ok(√ y panel /	the approprime Appropr	ortion S) Measured B-N Oriate) c): Inverter Disportate) ration Details	. Watt play :
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV 1kV < V <= 69 kV 69 kV < V <= 161 kV Power Generated Current by SPGS (dec) Manual Isolation d) Other Observation (E) Test Equipment Interpretation Signature:	ge Distor E 519:2 by SPC during S on Switc ions/Re Used: ; M	asured at portion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the semants (if any) aake:	Condition SPGS OF SPGS OF As per IEE The in the inversional load): Me ack-up System System Agency Agency	during loo	Vo Voltage -N /Not Ok(\varphi) y panel / -ss/No (\varphi)	Itage Distance Level: THD (% Y-N The approprometer of the approprometer) The approprometer of the appropro	ortion S) Measured B-N oriate) c): Inverter Disportate) ration Details ame :	. Watt play:
Permissible Voltage (As per IEEE Voltage Level V < 1.0 kV 1kV < V <= 69 kV 69 kV < V <= 161 kV Power Generated Current by SPGS (dec) Manual Isolation d) Other Observation (E) Test Equipment Information (Signature:	ge Distorer Services of the By SPC during Strain Switch Switch Switch Switch Switch Switch Switch By	asured at portion Limits 2014) THD (%) 8.0 5.0 2.5 GS (as available of SPGS ON without the semants (if any) aake:	Condition SPGS OF SPGS OF SPGS OF As per IEE The in the invertional is the invertional invertional is the invertional invertional is the invertional invertional is the invertional i	during load and the second sured in the second sured sured in the second sured sured in the second sured	Vo Voltage Voltage	Itage Distance Level: THD (% Y-N The approprometer of the approprometer) The approprometer of the appropro	ortion S) Measured B-N oriate) c): Inverter Disportate) ration Details ame :	. Watt play:

This sheet is to be used for one inverter. For multiple inverters, kindly use multiple sheets.