Selection of Developers for Setting up of 40 MW/80MWh Standalone Battery Energy Storage Systems in Kolkata under Tariff Based Competitive Bidding RfS No. ED(PM)/2025-26/266 dated 30.07.2025, Tender Search Code on ISN-ETS: CESC-2025- TN000001

	Clarifications-1 to Bio	dder's Queries		Dated: 18-09-2025
Sr. No	Document Name and Clause No.	Existing Clause	Rationale/Justification for Amendment/ Clarification sought	CESC's response
			We kindly request ESC to confirm how the process will be done i.e. whether the company / SPV holding this particular BESS project will be transferred to CESC or whether only the project will be handed over to CESC.	The BESS assets shall be transferred to CESC on Expiry Date of BESPA without any future financial obligation to CESC with operational battery capacity at 70% of the rated capacity as per RTS & BESPA.
1	RFS Clause 3.6	After the expiry of the Term of the BESPA, the Project will be transferred to CESC at Re. 1 without any financial obligations to CESC in working condition with defined energy throughput at the end of the term on a "as is where is" basis, in line with the provisions of the BESPA.	Also, kindy confirm regarding the GST inputs / benefits which will be available for the project. Will the same also be passed on to CISC. Kindy confirm.	Tariff to be quoted in the financial bid shall be excusive of GST (for offering storage capacity).
2	RFS Clause 3.2	This RTS is technology agnostic on the nature of battery storage system being opted by the BESSD, as long as it meets the definition of BESS under this RTS and the required performance criteria under the RTS and BESPA.	Kindly confirm whether the bidder is permitted to change the battery storage technology during the BESPA Tenure.	BESSD may change the battery storage technology with prior approval from CESC as long as it meets the definition of BESS under this RIS and the required performance criteria, safety regulations as applicable under the RIS and BESPA.
		The Project should be designed for interconnection with the CESC Network at 38kV Bus at New Cossipore Substation ("NCSS") in accordance with the prevailing WBER. Regulation, if any, in this regard. For interconnection with the CESC Network and metering, the BESS obtail abide by all lose and regulations framed under the Electricity Act, 2003 including	We request the following clarifications regarding the bay at the substation end:	
		the applicable Grid Code, Grid Connectivity Standards, Regulations on Communication System for transmission of electricity and other Regulations/Procedures (as amended from time to time) issued by WBERC and Central Electricity Authority (CEA).	1. Scope of Bay Construction:	
3		and order regulationly recognize (as attended not must be than loaded by when, and certal accentral executive) and order and executive partners (as the complete of the requirements of referent authority regarding charging and synchronization. The detailed network diagram is enclosed herewith at Annexuse — 2.	It allows to wap customacouncy in planes confirmation/augmentation at the substation will be carried out by CSEC on its own including buy or to be constructed by MESO only Augo, Lingly confirm in case if CSEC will construct by at S2 end, what will be the applicable charges and BGs payable / to be submitted by Bidder for same.	No additional 33MV bay is required at CESC's New Cossipore Substitation (NCSS). The 33MV cables (2 circuits, each of at least 25 MW), total 50 MWA) will be connected to the existing 33MV GS withchboard emanating from the 33MV intermediate bus (with incoming & outgoing 33MV circuit breakers) at the ESS end, via CFIPT collect at the MCSS end.
	RFS Clause 7.1			Connection sequence: Battery Bank \Rightarrow PCS \Rightarrow IDTs \Rightarrow 33KV Intermediate Bus (with incoming & outgoing 33kV circuit breakers) \Rightarrow 2 circuit (each 25 kWA, total 50 kWA) \Rightarrow CT/PT cubicle \Rightarrow termination at existing CESC 33kV GIS switchboard. The entire connection, from the Battery Bank up to termination onto the CESC's GIS switchboard, shall be in the bidder's scope. CESC has tentatively indicated this in the SLD given in the Annexure D of the RIS.
4			(b) Kindly share estimated costs payable to CESC, If any for bay construction and confirm if any guarantees or performance securities are also required for connectivity. Also, considering the new draft is under process for connectivity, so kindly confirm if the cost is to be considered in line with same.	
			2. Scope of Bay Q&M: Please confirm whether bay Q&M will be under CESC's scope at SS end or BESSD's scope and also,confirm the applicable annual charges & scope of same.	Pt. 2: The 33kV bay of CESC ends at cable spout. The circuit breaker (CB jat NCSS will be maintained by CESC. The cable termination, at the NCSS end bay (33kV CB), related issues to be addressed by the BESSD.
5	RFS Clause 7.6	The BESSO will be required to apply for connectivity at the identified substation in terms of as per applicable Regulations of WBERG, within 30 days of issuance of LoA, and shall furnish copies of the application, to CESC within 7 days of submission of beat application, to see the BESSO Bids to obtain connectivity as the identified substation, the same shall be immediately notified by the BESSO to CESC. All the requisite costs associated with obtaining connectivity shall be borne by the BESSO.	We request CESC to kindly confirm the applicable cost & BGs applicable to secure the connectivity at these particular substations to connect the BESS project.	No additional cost & BGs will be involved. However, BESSD has to ensure and develop appropriate and necessary connectivity related infrastructure as per the scope of work mentioned in the RIS.
6	RFS Clause 20.1	Land identification and possession shall be in line with Clause 6 of the Rfs, and CESC shall facilitate usage of land to the BESSD. The tentative site plan is provided in Annexure D of the RfS	Kindly confirm that CESC will provide the encumbrance free clear land for development of BESS.	CESC shall provide encumbrance free land through Right-to-Use agreement as per RfS & BESPA. As per clause 20 of RfS, entire land has to be developed by the BESSD as usable land. BESSD has to carry out all the necessary checks / removal / demolition of overground / subsoil
				materials, if any, for timely commissioning of the project.
7	RFS Clause 20.4	CSSS shall make the land available to BESSD with preliminary demarcation, upon signing of Right to Use Agreement as per clause 20.3 above on as lightwere is basis. The entire scope of Land development, including construction of boundary wall, approach road (paging) be inharding the load of the requisite fire interior and all other equipment up to the mine retrance of the project site, and power/control cable trenches (Cable trench route to be finalized in consultation with CSSQ as required for successful exercised and commissioning of BESS at project site ability to the PESSD. Thread host cutting as per relevant taw, clearing and groubing, along with demoliton of any obstructions or facilities, land filling, removal of scrap materials, structure, water and debries, as applicable and all other necessary coll works required to facilitate the commencement of construction activities at the project site shall be in BESSD's scope.	to be developed at plant end only and also, the circuit breakerts etc to	The BESSD's scope is upto 33kV spout of 33kV CB at NCSS. The same has been shown in the tentative SLD (Annexure D of RIS)
8	RFS Clause 3.5	The BESSD shall take separate, metered connection for the Auxiliary Power load of BESS from CESC at its own cost. Bill will be raised by CESC to the BESSD on monthly basis for payment with respect to Auxiliary Power .	Kindy confirm whether auxiliary power can be supplied at 111V/33IV at the interconnection point along with provision that allowing BESSD for installation of a separate meter for auxiliary usage at interconnection point and the same can be billed by Discom.	Successful bidder shall apply for auxillary power as per regulations. CESC will provide a separate meter for auxiliary usage at the appropriate voltage. For loads up to 150 kVA, an It connection will be provided; for loads more than 150 kVA upto 1500 kVA, an If supply (a VI) will be arranged, as per the RIS and extant WBACT explations. The supply voltage leve shall be determined based on the load requirement during the application process shall be determined based on the load requirement during the application process shall be provided by the state of

			As per this clause, BESSD is required to obtain a separate metered connection for auxiliary power. Kindly confirm the following details for cost estimation:	
9	RFS Clause 3.5	The BESSD shall take separate, metered connection for the Auxiliary Power load of BESS from CESC at its own cost. Bill will be raised by CESC to the BESSD on monthly basis for payment with respect to Auxiliary Power.	Applicable infrastructure cost for auxiliary connection payable to CESC.	Saccesdad bidder shall apoly for auxiliary gover as per regulations. CSC will provide a compareter for auxiliary usage at the approxime trollage. For loads up to 150 MA, and T. of will be provided, for loads more than 150 MA upo 2500 MA, an IT supply (6 MV) will be arranged, as per the Sfall extensive Mester Cegulations. The supply voltage level shall be determined based on the load requirement during the application process. All charges for the upophs, such as forestic Charges, shall be some by the BESSD. The meter room, as specified in
			Applicable security deposit, if any.	the RfS, shall be provided by the BESSD. CESC may waive the Security Deposit (SD) subject to necessary approval. The BESSD shall be charged on a monthly basis as per actual consumptio
			Any other recurring or one-time charges.	necessary approval. The sessor shall be charged on a monthly basis as per actual consumption
			Applicable tariff category and additional charges for auxiliary supply.	LT/HT Industries, as per CESC's Tariff order
10	RFS Clause 43.26	"INTER-CONNECTION POINT/ DELIVERY/ METERING POINT/POINT OF COMMON COUPLING (PCC)" shall mean 33 MV switchboard of CESC's New Cossipore Substaion, where the power to/from the Project is injected/delivered from/into the CESC, network (indicing the dedicated intelled) connecting the Project with the substation system) as specified in the RIS. A Single Line Diagram showing interconnection point is enclosed as Annexure D of this RIS. Metering shall be done at this interconnection with interconnection with enterconnection with reteremental variety and and metering, the RESIS shall abide by the relevant WEIRC Regulations, Grid Code and Central Electricity Authority (Installation and Operation of Meters) Regulations, 2003 as amended and revised from time to time.	Sindly confirm that the scope of bidder is up to 33 NV side of 55 and and beyond that the step up of power including power traft as applicable to step up will be in scope of GSS: including the cost and BESSD scope only includes the scope up to 33 RV side at Substation.	CESC confirms that the scope of bidder is up to 33 kV side cable termination at CESC's I Cossipore Substation end.
11	RFS clause 15	Note: The BESSO should apply for all the necessary approvals, permits and clearances not more than 90 days from the Effective Date of the BESSO, which shall be complete in all respects, incorporating the clarifications/change as required by the concerned authorities. The above timeline shall be adhered to, in order to examine cases where the BESSO faces delay in grant of the necessary approvals and permits. for a period substantially greater than the standard period of grant of approval by the respective organizations.	We would like to highlight here that post filing of application for approvals, the delay in process may lead to delay in SCSD of project. Accordingly, we kindly request CESC to incorporate provisions in this clause for extension in case of delay in the grant of necessary approvals and permits.	Existing Clause shall prevail (Please refer BESPA clause 3 for appropriate reliefs, if any)
12	General Query	Status of Bay	Kindly confirm whether currently the bay is available at Substation for interconnection of the bess project or the same will be constructed at later stage post award of project.	The 38W cables (2 dats each of at least 25 M/A, total 50 M/A) shall be terminated at existin 33W GIS did at CESC's New Cossipore Substation. The bay G38W GIS sanell is ready for use.
			Also, kindly confirm the time period which CESC required in case bay will be developed at SS end by CESC post any applicable payment payment / deposit by BESSD.	The day (Sales and participation asc.
13	General Query	Length of TL	Kindly confirm the distance / length of Transmission line to consider from BESS proposed location to interconnection point.	33 kV cable length around 500 m each.
14	General Query	Applicable cost towards state nodal agency	Kindly confirm applicable charges payable to State Nodal Agency including registration charges, annual fees, and any separate 8G requirements under state Policy, in addition to PBG to be submitted to CESC.	BESS will be embedded in the CESC's network. Not connected to STU network. No additions to 8 dis will be involved. BESSD has to ensure and develop appropriate and neces connectivity related infrastructure as per scope of work mentioned in the RIS. Howe BESSD has to follow the WBERC regulations, as applicable.
15	General Query		Please clarify the Scope of Construction of Bay and related Evacuation Infrastructure at the point of Interconnection.	I2 circuits, each of at least 25 MWI, total 30 MWI) will be connected to the existing 334V GI southboard manning from the 334V intermediate bus (with microming & outgoing 334V GI breakers) at the BESS end, via CT/PT cubicle at the NCSS end. Connection sequence: Battery Bank > PCS - 910Ts > 338V intermediate Bus (with incoming outgoing 334V GF the breaker) > 2 Circuits (each 225 MWI, total 50 MWI) > CT/PT cubicle termination at existing CESC 318V GIS switchboard. The entire connection, from the Battery Bank up to termination onto the CESC's GIS switchboard with be in the bidder's scope. CESC has tentatively indicated this in the SLD giv in the Annexure D of the RIS.
16	RFS Clause 6.1	Land required for construction of BESS will be provided by CESC at the above location in as is /where is basis.	Kindly specify the land arrangement in more detail. If the land is available, please share the total land area along with the corresponding KMZ file.	Land will be made available after Right to Use agreement and other requirements as per BI and RfS. KMZ file is given as reference is already uploaded as Addendum-5 in ISN-ETS portal.
17	RFS Clause 8.1. e)	The BESSD shall guarantee a minimum system availability of 95% on monthly basis.	Kindly consider the BESS System availability of 95% on annual basis instead of monthly basis.	Existing Clause shall prevail.
18	RFS Clause 8.2. c)	Shortfall in meeting Monthly RIE	REE 90% is not feasible to achieve. Unlike other silmilar BESS tenders request to reduce the REE requirement to 85%.	Bidders are kindly requested to read roundtrip efficiency (REE) of 90% as 85% on mon basis" which shall be applicable in RFS and BESPA
19	RFS Clause 11.3	BESS shall be capable of operating in the frequency range 47.5 to 52 Hz and be able to deliver rated output both in charging and discharging mode in the frequency range of 49.5 Hz to 50.5 Hz.	Grid forming inverters in India are provided by very few vendors and currently it is not understood properly frequency operation exp. for addressing these operations.	Existing clause shall prevail.
20	RFS Clause 8.1.e.iii	Auxiliary Power	Auxiliary power can be tapped from the same 5/s with a separate metering arrangement?. PI confirm	Successful bidder shall apply for annillary power as per regulations. ESEs will provide a expensed for auxillary usage at the appropriate sorbage. For leads up to 150 MA, an IT conserved will be provided for loads more than 300 MA upot 2500 MA an IT supply (81 Vi) will be arranged, as per the RS and extent WBERC regulations. The supply voltage level shall be arranged, as per the RS and extent WBERC regulations. The supply voltage level shall be determined based on the load requirement furing the application process. All charges for th supply, such as Service Charges, shall be borne by the BESSO. The meter room, as specified the RS, shall be provided by the BESSO. CEST may waite the Security Deepoil (8) object to necessary approval. The BESSO shall be charged on a monthly basis as per actual consumption.
21	8.1.e.iii	Auxiliary Power Tariff	What is the applicable tariff category for auxiliary power consumption?	LT/HT Industries, as per CESC's Tariff order
22	General Query		Will it be fixed or subject to revision? Pls share the co-ordinates of the Interconnection Point.	New Cossipore Substation 22.624264845494007, 88.37010890641494
			Request to provide the following documents related to land parcels -	
			, , , ,	As mentioned in RfS (clause 8.6 of Annexure A), Soil Test is in BESSD's scope.
			a. Soil Investigation report	
			Soil Investigation report	As per clause 20 of Rfs, entire land has to be developed by the BESSO as usable land. BESSO to carry out all the necessary check; removal / demolition of overground / subsoil materials any, for timely completion of the project. Tentative SID is given in Annexure D of the RES. Site sera has been modified to 5000 s.a.m. from 5800 s.a.m. due to technical reasons.

1 1		İ		
23	General Query		d. KMZ file of the SS along with vacant land earmarked for BESS	KMZ file is already uploaded as addendum-5 in ISN-ETS portal.
	derein eacry		 Please clarify that the land for approach road is under the possession of CESC and there would not be any ROW issue for creation of approach road. 	Approach road from NCGS main gate to BESS site is under possession of CESC. Approach road has to be developed by BESSD.
				As mentioned in RfS (clause 8.6 of Annexure A), Soil Test is in BESSD's scope.
			f. Earth Resistivity Report	As per clause 20 of RfS, entire land has to be developed by the BESSD as usable land. BESSD has to carry out all the necessary checks / removal / demolition of overground / subsoil materials, if any, for timely completion of the project.
			Please specify the type of road. From the main road to the plant, ROW is in whose scope.	Approach road from NCGS main gate to BESS site is under possession of CESC. Approach road has to be developed by BESSD.
24	General Query		We kindly request that the submission deadline be extended by three weeks from the date the pre-bid queries are released.	No extension shall be given.
			AlS or GIS	The existing bay at CESC's end is 33kV GIS panel.
			Whether existing SAS system is available for integration of additional bay?	The existing bay at CESC's end is 33kV GIS panel. This panel is connected with the existing SCADA
			In existing RTU spare terminals are available for data transfer of this additional bay to SLDC?	Existing RTU can't be used by the Bidder. The specific requirement is given in the RfS.
			Is readily spare bay available in the Substation OR is there space available in the substation for bay construction?	The bay (33kV GIS panel) is ready for use.
25	General Query	General Substation/ Land related	Is there any space available in existing Main Control room for electrical panel for additional bay? OR control room extension possible	Space is available for installation of CT/PT cubicle panel.
25			Boundary or Area belongs to any agricultural science dept., Forest dept. and land acquired by local builder for Residential/ Commercial area?	Under the ambit of CESC. Hence, no RoW issue is envisaged.
			Busbar panel protection is there OR we have to provide	BESSD needs to provide the all kinds of protection system for BESS including the line differential protection for the connecting cable between BESS end and CESC's 33kV GIS end (as per RfS). The existing 33kV GIS Bd at CESC's end has busbar protection.
			Which type of connected line - T/I line or cable to be arranged? PI confirm.	33 kV Cable, Length is around 500 m for each circuit.
			What shall be the distance from substation to BESS system land provided?	
	RFS Clause 3.5	BESS from CSCs at loo en cost. Bill will be raised by CSC to the BESSO on monthly balls for payment with respect to Ausiliary Power	Request to please provide clarity on the below –	Successful bidder shall apply for auxiliary power as per regulations. CESC will provide a separate meter for auxiliary usage at the appropriate voltage, For loads up to 15 DMX, an LT connection will be provided; for loads more than 15 DMX value pt 500 MX, an HT supply (st Ny will be arranged, as per the RIS and estant WBERC regulations. The supply voltage level shall be determined based on the load requirement during the application process. All charges for the supply, such as Service Charges, shall be borne by the BESSO. The meter room, as specified in the risk, shall be provided by the BESSO. CESC may wave the Security Deposit (SD) subject to necessary approval. The BESSO shall be charged on a monthly basis as per actual consumption.
			i. Applicable infrastructure cost for	
			auxiliary connection payable	
26			ii. Applicable security deposit, if any.	
			iii. Any other recurring or one-time charges.	
			iv. Applicable tariff category and additional charges for auxiliary supply.	LT/HT Industries, as per CESC's Tariff order
27	RFS Clause 7.2	The maintenance of interconnection network with CESC network shall be responsibility of the BESSD, to be undertaken entirely at its cost and expense. The entire cost of network development including cost of construction of line / Cables, maintenance cost etc. and any other charges from the Project up to and including at the Interconnection Point will be borne by the BESSD or Berger to a maintenance of the Cables of the BESSD for supply of Power an "on Demand" basis, having single point of Injection at Interconnection/ Ofelvery Meeting Point. The Project shall also comprise auxiliaries and associated facilities, bay(s) for transmission system in the their switchyard, declicated line(s) up to the injection point and all the other assets, ballings/instructures, explainment, plant and machinery generating of the BESS), Bildings of raised assets required for the efficiency for the project of the purpose of supply of power to CESC.		No additional 331V bay is required at CESC's New Costopore Substation (NCSS). The 331V cables (2 circuits, each of at least 25 MVA, total 50 MVA) will be connected to the existing 333V GIS switchboard emanating from the 231V intermediate bus (with incoming & outgoing 331V circuit breakers) at the BESS end, via CT/PT cubicle at the NCSS end. Connection sequence: Battery Bank + 9 CS + 0TD: + 233V intermediate Bus (with incoming &
				Connection sequence: stately skin \rightarrow VLS \rightarrow IDL \rightarrow 3 abs VI intermediate Blus (with incoming & Ourgings 33AV Orat breakers) \rightarrow 2 courts (see the 25 MWA), total SD MWA) \rightarrow CT/PT cubdle \rightarrow termination at existing CESC 33AV GS switchboard. The entire connection, from the Battery Bank up to termination onto the CESC 5s switchboard, shall be in the bidder's scope. CESC has territatively indicated this in the SLD given in the Amesure-D of the Rfs.
		I		

RFS Clause 8.1.e.iii	The BESSD shall guarantee AC to AC roundtrip efficiency (REE) of 90% of on monthly basis.	Kindly provide the detailed procedure for RtE measurement: This should include the following:	As per RfS
		Will auxiliary loads be included or excluded in the calculation?	Auxiliary will not be included in REE calculation. Bidders are kindly requested to read roundtrip efficiency (REE) of 90% as 85% on monthly basis" which shall be applicable in RFS and BESPA
		What is the sampling duration (single cycle vs averaged over month)?	Please refer RfS
	The procurement shall be in power (MW) terms. The BESSD shall install, operate and maintain the BESS to offer facility to the CESC to charge and	How will Availability of the Project be monitored and verified — will it be based on SCADA data, control signals, or third-party metering?	Please refer to clause no. 8.1.e (ii), it is clarified that the Actual nijection/Drawal shall be as per measurement as per ABT meter and Scheduler Injection/Drawal as per schedule provided by CESC.
	discharge the BESS on an "on demand" basis. The BESSD shall guarantee a minimum system availability of 55% on monthly basis. The BESSD shall pay the fliquidated damages for any shortfall in monthly availability below 5% and shall duly sup- such damages to CESC. Amount of such liquidated damages shall be twice the Capacity Charges for the capacity not made available.		
RFS Clause 6.3 RFS Clause 20.4 Annesure A	BESSD shall make necessary arrangements for approach roads, balance of plant, power/control cable trench (table trench route to be finalized in consultation with CESC) etc. at the site without hordering the activities of the New Cospine Substation (TNCSS). As BESS' are prone to fire hazard, the BESSD shall provide suitable means such as fire barriers between switchiger and BESSD of small provides until the means such as fire barriers between switchiger and BESSD of small provides until the means such as fire barriers between switchiger and BESSD of small provides until the means such as fire basis. The memory of the special provides of the special provides of the provides of the provides of the provides the tender and all other equipment) so to the main entrace of the projects that approver/control cable trencher could be trench route to be finalized in consultation with CESD, as required for successful erection and commissioning of ESSS a project is final bite in the scope of BSSD. The and both cutting as per relevant law, clearing and grubbing, along with denotion of any delarations or facilities, land filling, removed of strop materials, structures, usake and delaris, as applicable and all other necessary oil work required to facilities the commissioning of construction activities at the project size shall be in BESSD's scope An analysis of the functional and performance requirements of this specification and or of sits surveys, essign and engineering may lead the bidders to conclude that additional items are required that are not	Kindly provide the infrastructure available in the substation to estimate accurate costing and identifying the scope of work. This is required to arrive at an accurate estimate of capacity charge to be quoted.	Please refer the RIS.
General Query		Clarification required on BOOT model and scrapping	The project is under Build, Own, Operate, Transfer (BOOT). The BESS project shall be transferred to CESC on Expiry Date of BESPA without any future financial obligation to CESC with operational battery capacity at 70% of the rated capacity as per RIS & BESPA. Safe Disposal on unit Batteries from the BESS shall be applicable on BESSO during the period of the BESPA as per RIS and relevant extant standard/guidelines/regulations.
	RFS Clause B.1.e.i RFS Clause 6.3 RFS Clause 6.3 Annexure A	The procurement shall be in power (MW) terms. The BESSD shall install, operate and maintain the BESS to offer facility to the CESS to charge and discharges the ESS on an "ro-demonal" basis. The BESSD shall install, operate and maintain the BESS to offer facility to the CESS to charge and discharges the ESSD shall part the liquidated damages for any shortfall in monthly availability below 59% and shall day pay such damages to CESS. Amount of such liquidated damages shall be twice the Capacity Charges for the capacity not made available. BESSD shall make necessary arrangements for approach roads, balance of plant, power/control cable trench (cable terench road to be familiared in consultation with CESC) etc. at the site without hindering the activities of the New Cosipore substation "TNCSS"). As BESS are proon for heazard, the BESSD shall provide substation entry CESS. The barriers between switchyrad and EESS to ensure adequate safety in terms of Annexure A for this RIS. CESC shall make the land available to ESSS with previously referrance you capacity of the RIP of the R	RFS Clause 8.1.e.ii The BESSD shall guarantee AC to AC roundtrip efficiency (RtE) of 90% of on monthly basis. Will auxiliary loads be included or excluded in the calculation? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over month)? What is the sampling duration (single cycle vs averaged over months? What is the sampling duration (single cycle vs averaged over months? What is the sampling duration (single cycle vs a

Reference of the control of the cont				
Part of the control control of Section Control				There is no conflict in the clause 3.1 & 3.4. Bidder to recheck.
Section of grant and an analysis of	32	General Query	Clarification required on scope of charging & discharging (Clause 3.4 & Clause 3.1 – suspected conflict)	required to set up a Battery Energy Storage System (BESS), with the primary objective of making the energy storage facility available to CESC for charging/discharging of the BESS, on an "on
National General General Court of Control General Court of Control General Court of				Scheduling of power for such charging/discharging as well as the obligation of providing
Property of the Control Country Control Country Property of the C				CESC will provide the schedule and BESSD will execute the charging & discharging of BESS.
Secretar Gurry According Gurry Accordi	33	General Query	Full capacity / Part capacity bidding allowed?	Bidders must quote for full capacity. There will be one successful bidder.
Social Curry It is possible and the control of the properties on the Chipter of Section (Curry Curry) Central Curry Central	34	General Query	Interconnection of 33kV cable, extra 33kV bay at CESC required or not?	12 circuits, each of at least 25 MVA, total 50 MVA) will be connected to the existing 334V circuit breakers] as withoutboard emansing from the 334V intermediate bus (with incoming & outgoing 334V circuit breakers) at the BESS end, via C/IPT cubicle at the NCSS end. Connection sequence: Battery Bank - PCS -> IDTs -> 334V Intermediate Bus (with incoming & outgoing 334V circuit breakers) -> 2 circuits (seek > 25 MVA, total 50 MVA) -> CT/PT cubicle -> termination at existing CESC 334V GIS switchboard. The entire connection, from the Battery Bank up to termination onto the CESC's GIS switchboard, salls in the bidder's scope. CESC has tentatively indicated this in the SLD given
Control Query Contro	35	General Query	RtE 90% is on higher side. Is it possible to consider 85% RtE?	Bidders are kindly requested to read roundtrip efficiency (RtE) of 90% as 85% on monthly basis" which shall be applicable in RFS and BESPA
only for EAP Now many cycles considered for Ancillary Services What is been for SERSA RESPA RESSO in required to ensure 2 cycles of BESS usage part day. Cycle calculation may be carried and on day has been constructed and calculations may be carried and on day has been constructed in RES (status E. B. of Anneurum A.), Soil Test is in RESSO) scope. An emerationed in RES (status E. B. of Anneurum A.), Soil Test is in RESSO) in Sequence of the proper. Soil test report (testation required for initial quoting) An emerationed in RES (status E. B. of Anneurum A.), Soil Test is in RESSO) in Sequence of the proper. Introver / PAT which will be considered? Control Query Control Query Soppe of removal of structures, debris Soppe of removal of structures, debris Soppe of removal of structures, debris Soppe of stranging construction water/power, boreveil permission, tree softened Query Control Query Soppe of stranging construction water/power, boreveil permission, tree control Query Control Query Anistic Control Query Control Query Soppe of stranging construction water/power, boreveil permission, tree control Query Control Query Anistic Control Query Control Query Anistic Control Query Control Query Anistic Control Query Control Query Anistic Control Query A	36	General Query	Is penalty applicable on both System Availability & RtE?	Existing Clause shall prevail.
Sol test report (tentative required for initial quoting) As per clause 20 of MS, entire land has to be developed by the BESSD has to carry out all the recessary check of removal / demolition of overground / subsol materials, if any, for temporary common of the project. Turnover / PAY which will be considered? Solet and Cluery Type of 31XY switchboard to be considered – indoor/(Dutdoor? Indoor, to be installed at Switch-Cum-Control Room at BESS site. Sole of arranging construction water/power, borewell permission, tree castery) Ceneral Query Ceneral Query Ceneral Query Ceneral Query Ceneral Query Ceneral Query Assistance from CESC is required durin the system (cooling & Fire castery) Assistance from CESC is required during construction of cable trench Assistance from CESC is required during construction must be carried out in presence of CESC trial pits may be necessary. Cable specifications / GTP related query FRIS type cables—additional fire-retardant paint required? Fire-retardant paint to be applied The cable is in the bidder's scope. CESC has tentatively indicated that the requirement is 25 MMA per circuit, for 2 parallel circuits, the total is 50 MVA. Ceneral Query SOADA integration process Sorely Bond as an alternative to the Bank Gourantee for the EMD Sorely Bond as an alternative to the Bank Gourantee for the EMD	37	General Query	only for EA? How many cycles considered for Ancillary Services? What is	per RfS & BESPA. BESSD is required to ensure 2 cycles of BESS usage per day. Cycle
to carry out all the necessary checks / emonal / demolstion of overground / subsoil materials, if any, for timely completen of the project. 17				As mentioned in RfS (clause 8.6 of Annexure A), Soil Test is in BESSD's scope.
Scope of removal of structures, debris Shall be in bidder's scope. The structures will be shifted and stored (near the BESS size – to be allotted by CESI by selected Bidder. Scraphing will be done by CESI as owner of those Rems. Fype of 31kV Swiftshboard to be considered – indoor/Ourdoor? Indoor, to be installed at Switch-Cum-Control Room at BESS size. Scope of arranging construction water/power, borewell permission, tree unding clearances etc. Uninterrupted auxiliary supply is required run the system (cooling & Fire case) Assistance from CESC is required during construction of cable trench General Query Assistance from CESC is required during construction of cable trench Cable trench construction must be carried out in presence of CESC, trial pits may be necessary. FRIS type cable – additional fire-retardant paint required? Fire-retardant paint to be applied General Query Cable specifications / GTP related query The cable is in the bidder's scope. CESC has tentatively indicated that the requirement is 25 M/M, per circuit, for Japanille Circuits, the total is 30 M/M. Scraph Country SCADA integration process Expected Country Remover, standatone Machine is required at the construction for scheduling & viewing the BESS performance.	38	General Query	Soil test report (tentative required for initial quoting)	to carry out all the necessary checks / removal / demolition of overground / subsoil materials, if
Sope of removal of structures, Sebris altotted by CESC) by selected Bidder. Scrapping will be done by CESC as owner of those Items. Type of 33kV Switchboard to be considered – indoor/Outdoor? Indoor, to be installed at Switch-Cum-Control Room at BESS site. Sope of arranging construction water/power, borewell permission, tree cutting clearances etc. Indoor, to be installed at Switch-Cum-Control Room at BESS site. Sope of arranging construction water/power, borewell permission, tree cutting clearances etc. Indicate the cutting clearances etc. Indicate the cutting clearances etc. Indicate the cutting clearances etc. Assistance from CESC is required run the system (cooling & Fire CESC will provide N-1 redundancy in power. Assistance from CESC is required during construction of cable trench. Cable trench construction must be carried out in presence of CESC, trial pits may be necessary. FRIS type cable – additional fire-retardant paint required? Free-retardant paint to be applied General Query The cable is in the bidder's scope. CESC has tentatively indicated that the requirement is 25 MAVA per circuit; for Japaniled circuits, the total is 50 MVA. General Query Sound as an alternative to the Bank Guarantee for the EMD Surely Bond as an alternative to the Bank Guarantee for the EMD Surely Bond as an alternative to the Bank Guarantee for the EMD	39	General Query	Turnover / PAT which will be considered?	Existing Clause shall prevail.
Songe of arranging construction water/power, borewell permission, tree cating clearances etc. 43 General Query 44 General Query 45 General Query 46 General Query 47 General Query 48 General Query 49 Cable specifications / GTP related query 40 General Query 41 Cable specifications / GTP related query 42 General Query 43 Social provides that the requirement is 25 M/MA per circuit; for 2 parallel circuits, the total is 50 M/M. 46 General Query 47 General Query 48 Social Courty 58 Social Courty 59 Social Courty 50 Social Courty 59 Social Courty 50 S	40	General Query	Scope of removal of structures, debris	
43 General Query 44 General Query 45 General Query 46 General Query 47 General Query 48 Jeneral Query 49 Cable specifications / GTP related query 40 Cable specifications / GTP related query 41 SCADA integration process 42 Survey Bond as an alternative to the Bank Goarantee for the EMD 43 Survey Bond as an alternative to the Bank Goarantee for the EMD 44 Survey Sond as an alternative to the Bank Goarantee for the EMD 45 Survey Bond as an alternative to the Bank Goarantee for the EMD 46 Survey Sond as an alternative to the Bank Goarantee for the EMD 47 Survey Sond as an alternative to the Bank Goarantee for the EMD 48 Survey Bond as an alternative to the Bank Goarantee for the EMD 48 Survey Bond as an alternative to the Bank Goarantee for the EMD 48 Survey Bond as an alternative to the Bank Goarantee for the EMD 48 Survey Bond as an alternative to the Bank Goarantee for the EMD 48 Survey Bond as an alternative to the Bank Goarantee for the EMD 48 Survey Bond as an alternative to the Bank Goarantee for the EMD 48 Survey Bond as an alternative to the Bank Goarantee for the EMD 48 Survey Bond as an alternative to the Bank Goarantee for the EMD 48 Survey Bond as an alternative to the Bank Goarantee for the EMD 49 Survey Bond as an alternative to the Bank Goarantee for the EMD	41	General Query	Type of 33kV Switchboard to be considered – Indoor/Outdoor?	Indoor, to be installed at Switch-Cum-Control Room at BESS site.
44 General Query Assistance from CESC is required during construction of cable trench Assistance from CESC is required during construction of cable trench Assistance from CESC is required during construction of cable trench Cable trench construction must be carried out in presence of CESC, trial pits may be necessary. FRLS type cable – additional fire-retardant paint requiree? Fire-retardant paint to be applied General Query Cable specifications / GTP related query The cable is in the bidder's scope. CESC has tentableey, indicated that the requirement is 25 MVA, per circuit; for 2 parallel circuits, the total is 50 MVA. General Query SCADA integration proces EMS of BESS will not be connected to CESC's SCADA system. However, standatione Machine is required at CESC Control Room for scheduling & viewing the BESS performance.	42	General Query	Scope of arranging construction water/power, borewell permission, tree- cutting clearances etc.	In BESSD's scope as per R/S.
45 General Query FRLS type cable – additional fire-retardant paint required? Fire-retardant paint to be applied The cable is in the bidder's scope. CESC has tentatively indicated that the requirement is 25 M/W per circuit; for 2 parallel circuits, the total is 30 M/W. 47 General Query SCADA integration proces EMS of RESS will not be connected to CESC'S SCADA system. However, standatione Machine is required at CESC Central Room for scheduling & viewing the RESS performance.	43	General Query	Uninterrupted auxiliary supply is required run the system (cooling & Fire safety)	CESC will provide N-1 redundancy in power.
46 General Query Cable specifications / GTP related query The cable is in the bidder's scope. CESC has tentatively indicated that the requirement is 25 M/M per circuit; for 25 parallel circuits, the total is 50 M/M. 47 General Query SCADA integration process EMS of BESS will not be connected to CESC's SCADA system. However, standalone Machine is required at CESC Control Room for scheduling & viewing the BESS performance.	44	General Query	 Assistance from CESC is required during construction of cable trench	Cable trench construction must be carried out in presence of CESC; trial pits may be necessary.
40 General Query 47 General Query 48 SCADA Integration process Surely Bond as an alternative to the Bank Goarantee for the EMD 48 Surely Bond as an alternative to the Bank Goarantee for the EMD 49 When the Company of the Compa	45	General Query	 FRLS type cable – additional fire-retardant paint required?	Fire-retardant paint to be applied
49 Surety Bond as an alternative to the Bank Guarantee for the EMD AB Control District AB C	46	General Query	Cable specifications / GTP related query	The cable is in the bidder's scope. CESC has tentatively indicated that the requirement is 25 MVA per circuit; for 2 parallel circuits, the total is 50 MVA.
	47	General Query	SCADA integration process	EMS of BESS will not be connected to CESC's SCADA system. However, standalone Machine is required at CESC Control Room for scheduling & viewing the BESS performance.
	48	General Query		We only accept BG.